

# CUBIC EVOLUTION SUSPENDED | G5/P5



**DE** LED-Pendelleuchte. Direkt-indirekt oder rein direktstrahlend. Leuchtenkörper in minimalistischer Bauhöhe aus Aluminiumprofil. Oberfläche naturelxiert oder weiß, graphit, schwarz bzw. champagnerfarben lackiert sowie Alu poliert. Weitere Oberflächenoptionen siehe Lightnet-Surface-Collection oder RAL nach Wahl. Microprismenoptik mit optimierter Blendungsbegrenzung speziell für Office-Anwendungen. Satinierter Opaldiffusor für Allgemeinbeleuchtung mit max. Transmissionsgrad und homogener Lichtpunktauflösung. Indirektanteil mit innovativer Linsentechnologie für breitstrahlende Deckenaufhellung. Konverter in Leuchtgehäuse integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (1-10V, DALI, Touch-Dim, Casambi). Farbtemperaturen 2700K, 3000K, 3500K oder 4000K. Binning initial ≤ MacAdam 3. Farbwiedergabe CRI>80 oder CRI>90. Stufenlos höhenverstellbare Y-Seil- oder Parallel-Seilabhängung mit transparent ummantelter Zuleitung.

**EN** LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body with minimalist overall height made of aluminium profile. Surface natural anodised or white, graphite, black or champagne coated as well as polished aluminium. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Indirect light with innovative lens technology for wide-angle ceiling illumination. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperature 2700K, 3000K, 3500K or 4000K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height adjustable Y-cord suspension or parallel-cord suspension with transparent power supply cable.

**FR** Luminaire LED suspendu. Éclairage direct/indirect ou seulement direct. Corps du luminaire en profilé aluminium et épaisseur minimaliste. Surface anodisée ou laquée blanc, graphite, noir, champagne ou polie. Autres options de finition voir Lightnet-Surface-Collection ou RAL au choix. Diffuseur microprismatique optimisé pour un éblouissement limité et adapté aux bureaux. Diffuseur opale satiné pour un éclairage général et une transmission maximale et homogène. Composants indirects avec une technologie de lentille innovante pour un éclairage grand angle du plafond. Driver intégré dans le luminaire, au choix ON/OFF ou graduable (1-10V, DALI, Touch-Dim, Casambi). Température de couleur 2700K, 3000K, 3500K ou 4000K. Binning initial ≤ MacAdam 3. Rendu de couleur CRI>80 ou CRI>90. Filin et tendeur rapide réglable en Y ou filin parallèle droit avec câble d'alimentation transparent.




**PRODUCT-CODE:** C P5 A B E - 8 30 M - L900 - Y

PRODUCT FAMILY	- C: Cubic
TYPE	- P5: Suspended Direct-Indirect G5: Suspended Direct Only
OPTICAL SYSTEM	- A: Microprismatic, O: Opal Diffuser
SURFACE FINISH	- W: Snow White, E: Silver Anodised, U: Urban Graphite, B: Jet Black, H: Champagne Silver, P: Polished Aluminium
CONTROL GEAR	- E: On/Off, L: DALI, D: 1-10V, H: Touch-Dim, C: Casambi, M: Multisensor
COLOUR REND.	- 8: CRI>80, 9: CRI>90
COLOUR TEMP.	- 27: 2700K, 30: 3000K, 35: 3500K, 40: 4000K
POWER	- M: Medium Power, H: High Power
SIZE	- Luminaire Length in mm: L900, L1200, L1500
SUSPENSION	- Y: Y-Cord Suspension, K: 4-Cord Suspension
ON REQUEST	- Emergency Module, Radar Sensor, Cable colour: Red, Black




MICROPRISMATIC / DIRECT-INDIRECT



UGR≤19 (X=4H, Y=8H, S=0.25H)  
DIRECT: ca.60% INDIRECT ca.40%

L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
900	4950lm/41W	6700lm/56W
1200	6750lm/53W	9110lm/73W
1500	8540lm/65W	11580lm/90W


MICROPRISMATIC / DIRECT



UGR≤19 for Medium Power (X=4H, Y=8H, S=0.25H)  
DIRECT: 100%

L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
900	3230lm/26W	4610lm/37W
1200	4460lm/33W	6320lm/48W
1500	5680lm/41W	8090lm/59W

OPAL DIFFUSER / DIRECT-INDIRECT



DIRECT: ca.60% INDIRECT ca.40%

L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
900	4670lm/41W	6290lm/56W
1200	6650lm/53W	8980lm/73W
1500	8120lm/65W	10970lm/90W

OPAL DIFFUSER / DIRECT



DIRECT: 100%

L mm	Lumen/Watt Medium Power	Lumen/Watt High Power
900	2950lm/26W	4200lm/37W
1200	4360lm/33W	6190lm/48W
1500	5260lm/41W	7480lm/59W

Lumen Values: Luminaire luminous flux at 4000K/CRI>80. Other configurations on request.



MULTISENSOR CONTROL

EMERGENCY MODULE



SNOW WHITE

SILVER ANODISED

URBAN GRAPHITE

JET BLACK

CHAMPAGNE SILVER

POLISHED ALUMINIUM